

DENOX AWS HYDRAULIC FLUID

PRODUCT DESCRIPTION

Denox Hydraulic Oil is manufactured from high VI Base Oil and is fortified with an inhibitor system to provide a product which insures maximum performance in all aspects of hydraulic service. Anti-wear agents keep wear rate low on critical pump parts and rust corrosion problems are eliminated by the rust inhibitor. A foam suppression additive eliminates concerns over operating problems due to foam build up in the hydraulic storage tank even in high circulation rate systems with low residence times.

BENEFITS :

- Excellent EP Performance
- Good Demulsibility and Anti-Foam Properties
- Excellent Rust Protection
- Excellent Antiwear Performance
- Outstanding Oxidative Stability

APPLICATION :

Recommended for all hydraulic systems regardless of the operating pressure. Specifically designed for all hydraulic system which require antiwear protection for pump parts. Used in lubrication of plain and anti-friction bearing, airline lubricators, moderately loaded gear sets.

TYPICAL CHARACTERISTICS

HYDRAULIC GRADE	100
Density @ 15°C	0.89
cSt @ 40 Cls	99.4
cSt @ 100 Cls	10.5
Viscosity ASTM D-455	-
Viscosity Index	108
Flash Point	220
Pour Point	-20

